

# ZK-LED55A-2K-3.5MM

## 55 inch LED Splicing Screen



- 55-inch display with Full HD (1920 × 1080) resolution
- Direct-lit LED backlight with uniform brightness and no boundary shadows
- Original industrial grade IPS (DID) LED splicing panel
- Wide view of field: 178° (H) / 178° (V)
- Intelligent 3D noise reduction
- Stable and 7 × 24 hours continuous working
- Support software-controlled splice and USB upgrade



### Product Parameters

#### Panel Properties

|                   |  |
|-------------------|--|
| Screen Size       | 55 inch                                      |
| Backlight         | Direct-lit LED backlight                     |
| Resolution        | 1920 × 1080                                  |
| Screen Proportion | 16 : 9                                       |
| Brightness        | 500 cd/m <sup>2</sup>                        |
| Contrast Ratio    | 3000 : 1                                     |
| Response Time     | 8 ms   |
| Color Depth       | 10-bit 1.07 Billion colors                   |
| Life Span         | 60,000 H (typ)                               |
| Viewing Angle     | 178° / 178° (horizontal / vertical)          |
| Bezel Width       | 2.4 mm (top / left), 1.4 mm (bottom / right) |

\*The above are approximate values, and the actual distance is related to the product and installation.

#### Power

|                   |                           |
|-------------------|---------------------------|
| Power Supply      | 100 to 240 V, 50 to 60 Hz |
| Power Consumption | < 150 W                   |

#### Operating Environment

|                       |                             |
|-----------------------|-----------------------------|
| Operating Temperature | 0 °C to 40 °C               |
| Operating Humidity    | 10% to 90% (non-condensing) |
| Operating Hours       | 7 × 24 h                    |

Interface

|        |   |
|--------|---|
| Input  | USB × 1, HDMI IN × 1, DVI × 1, RS232 IN × 1 |
| Output | RS232 OUT × 2                               |

General

|                   |   |
|-------------------|---|
| Product Material  | Metal   |
| Net Weight        | 16.5 kg   |
| Product Dimension | 1213.6 × 684.4 × 88.9 (mm)                                    |
| Package Dimension | 1360 × 260 × 815 (mm)   |
| Way to Install    | Floor cabinet type, floor bracket type, and wall bracket type |

Else

|          |   |
|----------|---|
| Fittings | AC power cable, warranty card, network cable, hook, adjusting screw, remote controller (optional) |
|----------|---|

Dimensions (mm)

